



ORCO Pavingstone Permeable Chips

For Use With

Aqua-Bric® Interlocking Concrete Pavingstones

Description

ORCO Permeable Chips is manufactured washed 1/8" to 1/4" (#4 stone) angular aggregate that is screened and packaged by OBP for ORCO Pavingstones.

Uses

Use for joints on interlocking concrete pavers in residential, commercial and Industrial applications.

Packaging

500 lbs Super Sack
1000 lbs Super Sack
2000 lbs Super Sack

Coverage

500 lbs Super Sack - 250 sf
1000 lbs Super Sack - 500 sf
2000 lbs Super Sack - 1000 sf

Features and Benefits

- Meets gradation requirements of Bio-Aquifer Storm System (BASS), Specification for Construction (Section 02780).
- Hardness helps prevent breakdown of joint material under loading.
- Angular aggregate aids in paver interlock.
- Super Sack allows for calculation of quantity per job, limiting waste.
- Dry aggregate allows for quick and easy sweeping into joints (no down time waiting for aggregate to dry).
- Gradation helps to prevent wash out or blow out of joint material.

Directions for Use

1. Spread dry permeable chips evenly across pavement and sweep with a broom into joints.
2. Remove excess chips, then vibrate surface with plate compactor.
3. Repeat process until joints are full. This may need to be repeated 2 or 3 times.

Note: Permeable Chips should not be used as bedding material.