

A Division of ORCO Block & Hardscape

Tre

showcase the unexpected three pieces at a time. Fuse understated simplicity with dramatic contrast to reinvent a traditional villa ambiance.

TYPICAL APPLICATIONS: Plazas, Terraces, Entrances, Parking Lots, Streetscapes, Driveways

FINISH AND EDGES: Flat; Aged




STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
Express Set	80	5 x 10	5.25 x 10.50	N/A	64
		10 x 10	10.50 x 10.50		
		10 x 15	10.50 x 15.75		


80 mm = 3.125 in (3 1/8 in); ALL SPECIFICATIONS ARE APPROXIMATE.

Common Patterns:

HERRINGBONE - 3 SHAPES



ALTERNATING RUNNER



Additional Info:

Visit www.orco.com for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition). ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit Interlocking Concrete Pavement Institute (ICPI) at www.icpi.org Tech Spec #2 - Construction of Interlocking Concrete Pavements. In addition, ICPI Guide Specifications provide information for installation of larger pavers, slabs, permeable systems, and using alternative setting beds like concrete, mortar, and bituminous asphalt. ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at www.orco.com



A Division of ORCO Block & Hardscape
ORCO.COM

