



Promenade * Palazzo Collection







Promenade

Evoke the essence of a grand promenade with a smooth patchwork of opulent and functional pieces for a stately presence.


TYPICAL APPLICATIONS: Plazas, Terraces, Parking Lots, Entrances, Streetscapes, Driveways FINISH AND EDGES: Smooth; Bevel



STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	size (in)	STONES PER SQ FT	SQUARE FT PER PALLET
SMALL SQUARE	80	4 x 4	3.94 x 3.94	9.3	85
RECTANGLE	80	4 x 8	3.94 x 7.87	4.65	93
SQUARE	80	8 x 8	7.87 x 7.87	2.32	93
LARGE RECTANGLE	80	8 x 12	7.87 x 11.81	1.5	93
LARGE SQUARE	80	12 x 12	11.81 x 11.81	1.0	93
EXPRESS SET	80	ALL 5	ALL 5	N/A	95

80 mm = 3.125 in ($3\frac{1}{8}$ in); All specifications are approximate.

Common Patterns:





Additional Info:

Visit www.orco.com for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition). ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit Interlocking Concrete Pavement Institute (ICPI) at www.icpi.org Tech Spec #2 – Construction of Interlocking Concrete Pavements. In addition, ICPI Guide Specifications provide information for installation of larger pavers, slabs, permeable systems, and using alternative setting beds like concrete, mortar, and bituminous asphalt. ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at www.orco. com



A Division of ORCO Block & Hardscape ORCO.COM

🔽 🕖 🖸 in 🖿 7/18