

ORCO
**BLOCK &
 HARDSCAPE**
 Family Owned Since 1946

12 x 24 Stone

Offering a unique blend of functionality and design, these pavingstones can transcend a grandiose hardscape with a variety of colors.

TYPICAL APPLICATIONS: Patio, Sidewalks, Courtyard, Pathways.

FINISH AND EDGES: Smooth Finish; Micro Chamfer Edge (60mm only); Bevel (80mm only); No Chamfer (80mm only).




STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
RECTANGLE	60	12 x 24	11.81 x 23.61	0.5	124
RECTANGLE	80	12 x 24	11.81 x 23.61	0.5	93

60 mm = 2.375 in (2³/₈ in); ALL SPECIFICATIONS ARE APPROXIMATE.


80 mm = 3.125 in (3¹/₈ in); ALL SPECIFICATIONS ARE APPROXIMATE.

Common Patterns:

RUNNER



HERRINGBONE



Additional Info:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C1782 Standard Specification for Segmental Concrete Paving Slabs (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition).

For proper installation procedures, visit Interlocking Concrete Pavement Institute (ICPI) at icpi.org Tech Spec #2 – Construction of Interlocking Concrete Pavements. In addition, ICPI Guide Specifications provide information for installation of larger pavers, slabs, permeable systems, and using alternative setting beds like concrete, mortar, and bituminous asphalt. ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.



ORCO.COM

