



# ORCO Pavingstone Permeable Chips

For Use With

**Attraverso Interlocking Concrete Pavingstones**

## **Description**

ORCO Permeable Chips is manufactured washed 1/8" to 1/4" (#4 stone) angular aggregate that is screened and packaged by OBP for ORCO Pavingstones.

## **Uses**

Use for joints on interlocking concrete pavers in residential, commercial and Industrial applications.

## **Packaging**

2000 lbs Super Sack

## **Coverage**

2000 lbs Super Sack - 1000 sf

## **Features and Benefits**

- Meets gradation requirements of Bio-Aquifer Storm System (BASS), Specification for Construction (Section 02780).
- Hardness helps prevent breakdown of joint material under loading.
- Angular aggregate aids in paver interlock.
- Super Sack allows for calculation of quantity per job, limiting waste.
- Dry aggregate allows for quick and easy sweeping into joints (no down time waiting for aggregate to dry).
- Gradation helps to prevent wash out or blow out of joint material.

## **Directions for Use**

1. Spread dry permeable chips evenly across pavement and sweep with a broom into joints.
2. Remove excess chips, then vibrate surface with plate compactor.
3. Repeat process until joints are full. This may need to be repeated 2 or 3 times.

Note: Permeable Chips should not be used as bedding material.

**ORCO Pavingstone Plant**  
4545 Rutile St., Riverside, CA 92509  
Phone (951) 685-8498 - FAX (951) 685-5974