

# Diamante

Invoke a historical dramatic appeal or modern simplicity for an impactful presence.

**TYPICAL APPLICATIONS:** Pool Decks, Courtyards, Driveways, Sidewalks, Patios, Pathways

**FINISH AND EDGES:** Smooth; Bevel




STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
DIAMOND	60	6 x 13	5.57 x 13.20	2.5	81
VILLA SQUARE	60	4 x 4	3.94 x 3.94	9.3	114
VILLA RECTANGLE	60	4 x 8	3.94 x 7.87	4.65	124
VILLA SQUARE	60	8 x 8	7.87 x 7.87	2.32	124


60 mm = 2.375 in (2<sup>3</sup>/<sub>8</sub> in); ALL SPECIFICATIONS ARE APPROXIMATE.

## Common Patterns:


PARQUET 2




PARQUET 3



PARQUET 8



SQUARE



## Additional Info:

Visit [ORCO.COM](http://ORCO.COM) for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units and/or C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest editions).

More information on standards and installation procedures can be found by visiting the Interlocking Concrete Pavement Institute (ICPI) at [ICPI.COM](http://ICPI.COM).

The following ICPI Tech Specs provide guidance on proper installation procedures:

Tech Spec 2 - Construction of Interlocking Concrete Pavements.

Tech Spec 24 - Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems.

Tech Spec 25 - Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Non-Vehicular Residential Applications.

ICPI recommends using ICPI Certified Installers who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at [ORCO.COM](http://ORCO.COM).



ORCO.COM

