

EcotHex

A versatile permeable hexagon paver that efficiently manages stormwater runoff.

TYPICAL APPLICATIONS: Patio, Sidewalks, Courtyards, Pathways, Parking Lots.

FINISHES: Standard, Shot Blast (SB), Burnish, Burnish / SB.

EDGES: Micro Chamfer Edge.



STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
HEXAGON	80	9" Hex	9.06"	2.63	91


80 mm = 3.125 in (3 1/8 in); ALL SPECIFICATIONS ARE APPROXIMATE.

PERMEABLE SET REQUIRES OBP PERMEABLE JOINT CHIPS.

SAND-SET REQUIRES POLY JOINT SAND FOR JOINTS.

Common Patterns:

STANDARD HEX PATTERN



Additional Info:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition). ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit Interlocking Concrete Pavement Institute (ICPI) at ICPI.ORG.

The following ICPI Tech Specs provide installation guidance:

Tech Spec 2 - Construction of Interlocking Concrete Pavement.

Tech Spec 18 - Construction of Permeable Interlocking Concrete Pavement Systems.

Tech Spec 23 - Maintenance guide for Permeable Interlocking Concrete Pavers.

ICPI recommends using ICPI Certified Installers who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.

