

Villa

showcase the unexpected one piece at a time. Fuse understated simplicity with dramatic contrast to reinvent a traditional villa ambiance.

TYPICAL APPLICATIONS: Driveways, Patios, Sidewalks, Courtyards, Pathways, Pool Decks

FINISH AND EDGES: Smooth; Bevel




STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
SMALL SQUARE	60	4 x 4	3.94 x 3.94	9.3	114
RECTANGLE	60	4 x 8	3.94 x 7.87	4.65	124
SQUARE	60	8 x 8	7.87 x 7.87	2.32	124
LARGE RECTANGLE	60	8 x 12	7.87 x 11.81	1.5	124
LARGE SQUARE	60	12 x 12	11.81 x 11.81	1.0	124
EXPRESS SET	60	ALL 5	ALL 5	N/A	118


60 mm = 2.375 in (2\% in); ALL SPECIFICATIONS ARE APPROXIMATE.

Common Patterns:


RANDOM ASHLAR - 5 PIECE




3 PIECE HERRINGBONE



RANDOM ASHLAR - 4 PIECE



2 PIECE STEP-UP



Additional Info:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units and/or C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest editions).

More information on standards and installation procedures can be found by visiting the Interlocking Concrete Pavement Institute (ICPI) at ICPI.COM.

The following ICPI Tech Specs provide guidance on proper installation procedures:

Tech Spec 2 - Construction of Interlocking Concrete Pavements.

Tech Spec 24 - Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems.

Tech Spec 25 - Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Non-Vehicular Residential Applications.

ICPI recommends using ICPI Certified Installers who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.













