

12 x 24 Stone

Offering a unique blend of functionality and design, these pavingstones can transcend a grandiose hardscape with a variety of colors.

TYPICAL APPLICATIONS: Patio, Sidewalks, Courtyard, Pathways. FINISH AND EDGES: Smooth Finish; Micro Chamfer Edge (60mm only); Bevel (80mm only); No Chamfer (80mm only).




STONE SHAPE	THICKNESS (MM)	DESCRIPTION (IN)	SIZE (IN)	STONES PER SQ FT	SQUARE FT PER PALLET
RECTANGLE	60*	12 x 24	11.81 x 23.62	0.5	124
RECTANGLE	80	12 x 24	11.81 x 23.62	0.5	93

60 mm* = 2.375 in (2\% in); ALL SPECIFICATIONS ARE APPROXIMATE. *STRICTLY NON-VEHICULAR APPLICATIONS

80 mm = 3.125 in ($3\frac{1}{8}$ in); all specifications are approximate.

Common Patterns:





BASKETWEAVE

Additional Info:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures slab and plank pavingstones in accordance with ASTM C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest edition).

For proper installation and design guidance, visit the Interlocking Concrete Pavement Institute (ICPI) at ICPI.ORG.

Tech Spec 24 - Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems, provides information on commercial applications.

Tech Spec 25 - Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Non-Vehicular Residential Applications.

ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.











