

CHEVRON









Basketweave

Runner

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Pedestrian / Auto / Truck
4 x 18 Chevron	80	3.94" x 17.75"	67	144	2354	Micro Chamfer	Smooth	Ŕ

80 mm = 3.125 in (31% in); ALL SPECIFICATIONS ARE APPROXIMATE.

ADDITIONAL INFORMATION:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures slab and plank pavingstones in accordance with ASTM C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest edition).

For proper installation and design guidance, visit the Interlocking Concrete Pavement Institute (ICPI) at icpi.org.

The following ICPI Tech Specs provide installation guidance:

- Tech Spec 24 Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems, provides information on commercial applications.
- Tech Spec 25 Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Non-Vehicular Residential Applications.

ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM

▲ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.