

## **PROMENADE**

















3 Piece Herringbone

2 Piece Step-up

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Pedestrian / Auto / Truck
4 x 4 Small Square	80	3.94" x 3.94"	85	792	2940	Bevel	Smooth	
4 x 8 Rectangle		3.94" x 7.87"		432	3210			
8 x 8 Square		7.87" x 7.87"	93	216				
8 x 12 Large Rectangle		7.87" x 11.81"		144				
12 x 12 Large Square		11.81" x 11.81"		96				
Express Set		All 5	95	224				

80 mm = 3.125 in (3% in); ALL SPECIFICATIONS ARE APPROXIMATE.

## **ADDITIONAL INFORMATION:**

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units and/or C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest editions).

More information on standards and installation procedures can be found by visiting the Interlocking Concrete Pavement Institute (ICPI) at icpi.com.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.

The following ICPI Tech Specs provide guidance on proper installation procedures:

- Tech Spec 2 Construction of Interlocking Concrete Pavement.
- Tech Spec 24 Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems.
- Tech Spec 25 Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Non-Vehicular Residential Applications.

ICPI recommends using ICPI Certified Installers who are trained in paver standards, materials, and techniques.

▲ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.