



TURFSTONE



Turfstone

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Pedestrian / Auto / Truck
16 x 24 Turfstone	80	15.66" x 23.50"	124	48	2930	Flat	Smooth	

80 mm = 3.125 in (3 1/8 in); ALL SPECIFICATIONS ARE APPROXIMATE.

ADDITIONAL INFORMATION:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures turfstone paving units in accordance with ASTM C1319 Standard Specification for Concrete Grid Paving Units (latest edition) and tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition).

ORCO certifies that our turfstone units average minimum compressive strength exceed 5000 psi and average water absorption no greater than 10%.

For proper installation procedures, visit the Interlocking Concrete Pavement Institute (ICPI) at www.icpi.org.

The following ICPI Tech Specs provide installation guidance:

- Tech Spec 8 – Concrete Grid Pavements.

ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

⚠ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.