





SERPENTINE



Herringbone



Runner

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Pedestrian / Auto / Truck
5 x 9 Serpentine	60	4.43" x 8.86"	108	400	3080	Bevel	Smooth	 

60 mm = 2.375 in (2 3/8 in); ALL SPECIFICATIONS ARE APPROXIMATE.

ADDITIONAL INFORMATION:

Visit ORCO.com for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition).

ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit Interlocking Concrete Pavement Institute (ICPI) at icpi.org.

- Tech Spec 2 - *Construction of Interlocking Concrete Pavements.*

In addition, ICPI Guide Specifications provide information for installation of larger pavers, slabs, permeable systems, and using alternative setting beds like concrete, mortar, and bituminous asphalt. ICPI recommends using ICPI Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.com.

⚠ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.